Voorhees Planning & Zoning Department 2400 Voorhees Town Center Voorhees, NJ 08043



Hours: 8:30 am – 4:30 pm, M-F Phone: 856-429-0647

Email: rentals@voorheesnj.com

# RESIDENTIAL RENTAL APPLICATION (AKA RESIDENTIAL CHANGE OF TENANT)

Owner/Seller Name:	Please circle all applicable: RESALE RE		RENTAL			
Property Address:	Block: Lot: Qual:					
Name of Development:	Occupancy Date:					
Buyer/Tenant Name:						
Buyer/Tenant Phone:						
Buyer/Tenant Email:						
REQUIRED: Email where Certificate is to be sent:						
In-State Agent's Name:						
In-State Agent's Phone Number:						
In-State Agent's Email:						
Will someone be present during the inspection? *Someone				<b>ly</b> empty		
If <b>yes</b> , please provide that person's:	If <b>no</b> , the lock box combination is:					
Name:	Lock box location:					
Phone Number:						
Acknowledgement that you have received the C/O req	uirements:					
	Signature of Applicant					
Certificate Fees:						
Re-inspection Fees:       A separate fee will be charged for each re-inspection as follows.						
For rental units, an additional \$250 will be charged if fair of the initial inspection.	led items are not b	rought into com	pliance withi	n 30 days		
If any portion of the property is inaccessible during an inspection, the inspector will deem the inspection as "failed," and the \$75 re-inspection fee will be required to be paid prior to the scheduling of the first re-inspection, and \$150 for any re-inspection thereafter.						
Payment must be made using Cash or Check. Checks should be made payable to <b>Voorhees Township</b> .						
ZONING OFFICE USE ONLY						

Cash/Check #:

Date:

Amount Paid:

Day:

Date Paid:

Inspection Schedule for:

Collected by:

Time:





# **ANNUAL LANDLORD REGISTRATION FORM**

Annual Registration Fee: \$50 per unit

Property Street Address:		Voorhees, NJ 08043						
Block:	Lot:	Qualifier (if applicable):						
Owner/Landlord 1 Name:		Owner/Landlord 2 Name:						
Owner 1 Address:		Owner 2 Address:						
Owner 1 Phone:		Owner 2 Phone:						
Owner 1 Email:		Owner 2 Email:						
Emergency Contact:		Emergency Contact Phone:						
Rental Agency Name:		Rental Agency Contact Nam	ne:					
Rental Agency Address:								
Rental Agency Phone:		Rental Agency Email:						
Maintenance Contact Name	2:	Maintenance Phone:						
Type of Dwelling (Circle One								
Townhouse	Condominium	Duplex	Single-Family Dwelling					
<b>.</b>								
Applicant Signature:		<u> </u>	C A 11 .					
		Signature of Applicant						
Amount Paid:	ZONING OFF Date Paid:	ICE USE ONLY Cash/Check #:	Collected by:					

Department of Community Development 2400 Voorhees Town Center Voorhees, NJ 08043

Rental Property Information
Property Street Address:



Hours: 8:30 am – 4:30 pm, M-F Phone: 856-429-0647 Email: rentals@voorheesnj.com

Voorhees, NJ 08043

LEAD INSPECTION APPLICATION

\$50 Fee - Checks must be made payable to Voorhees Township

Property Block #:	Property Lot #:					
Property Qualifier	(if applicable):					
Property Type:	Single Family Dwelling	Townhouse	Condominium	Duplex	Apartment	
Landlord Informat	ion					
Name(s) of All Pro	perty Owners/Landlords:					
Landlord's Address	S:					
Landlord's Email:		Landlord's Phone:				
Emergency Contac	Emergency Contact Name:		Contact's Phone:			
<ul><li>provided to the mule earlier. The following</li><li>Dwellings cons</li><li>Dwellings that</li></ul>	red to undergo routine le nicipality. Inspections are ng properties are exempt structed during or after 1 have been certified free	e required every : 978, of lead-based p	3 years or upon cha	ange of tenar	nt, whichever is	
<ul> <li>Dwellings that lead violations</li> </ul>	lead-based paint is prese have been registered wi or have an open inspect a a valid lead-safe certific	th the DCA for a ion & no paint v	iolations,	either have	no outstanding	
-	that your property qualif rification of the exemption			reasons liste	d above, you	
			Signature o	f Applicant		
5 . 5		NING OFFICE US		Callerand		
Date Paid:	Amount Paid:	Casn	/Check #:	Collected b	<u>y:</u>	
i e				1		



# **RENTAL INSPECTIONS** FOR RESIDENTIAL PROPERTIES

All residential **RENTAL** properties will be inspected for the following items, at minimum: ☐ Building identification (see page 4 for specific requirements) ☐ Carbon monoxide detectors (see page 4 for specific requirements) ☐ Electrical panel has no visual defects or open spaces ☐ Operable door locks (1st floor sliding door must have backup lock or mounted bar or pin in multifamily dwellings) ☐ Operable, unbroken windows with locks (screens required May through October) ☐ Heat is functioning properly (68 degrees from October through May) ☐ Refrigerator and a means of cooking with exhaust for range ☐ Random sampling of outlets checked for electrical issues ☐ Outlets at kitchen counter and bathroom are properly functioning GFI outlets ☐ Heater and water heater checked for visual defects ☐ Filter in heater is clean ☐ Balconies and railings are in good repair ☐ Peeling or flaking paint, mold or mildew build up ☐ Screen on fireplace ☐ Anti-tip brackets on ranges (if installed after 1991) ☐ Front door security chain and peephole (only for multi-family dwellings of 4 units or more) ☐ Smoke detectors (See page 5 for specific requirements) If you have an alarm company, you must notify them that you are having an alarm test done so that the Fire Department does not respond.

For a complete list of all items that are subject to inspection, see N.J. State Housing Code 2003, Multi Family Dwelling Code Title 5, Code 10, Chapter 28.

**NOTE:** The property/unit must be VACANT at the time of inspection. If the inspector is unable to access any of the items listed above due to boxes, furniture, etc., a **rental certificate will not be issued** until the \$75 reinspection fee has been paid and the unit has successfully passed a reinspection.

#### **INSPECTION ITEM DETAILS**

#### **BUILDING IDENTIFICATION**

Sections 98.36 and 98.38 require that all dwellings, stores, or other principal buildings display the address number assigned by the Tax Assessor. The required Arabic numerals shall be:

- installed on the building itself and <u>not</u> on doors or windows (stick-on or self-adhesive numbers will not be accepted as permanent numerals);
- located at least thirty (30") inches above ground level on a contrasting background;
- of sufficient height to be legible from the street, with three (3") inches being the absolute minimum height required; and
- free of sight obstructions from the street.

#### CARBON MONOXIDE DETECTORS

Must be installed outside of (but within ten (10') feet of) each and every sleeping area. While most sleeping areas are in one section of a home, if there is a bedroom on a different level than the rest or beyond ten (10') feet of the other doorways, an additional carbon monoxide detector is required.

#### **FIRE EXTINGUISHER**

For purposes of this section, "portable fire extinguisher" shall mean a portable device, carried and operated by hand, containing an extinguishing agent that can be expelled under pressure for the purpose of suppressing or extinguishing fire, and is:

- 1. listed, labeled, charged and operable;
- 2. 2A10BC rated weighing not more than 10 pounds;
- 3. rated for residential use consisting of an ABC type;
- 4. on hangers or in brackets supplied by the manufacturer;
- 5. within 10 feet of the kitchen area, unless otherwise permitted by an enforcing agency;
- 6. located with the top of the extinguisher not more than five feet (1.53 meters) above the floor;
- 7. visible and readily-accessible, unblocked by furniture, storage, equipment, and other items;
- 8. in proximity of a room exit or travel way that provides an escape route to the exterior;
- 9. accompanied by an owner's manual or written information regarding the operation, inspection and maintenance of the extinguisher; and
- 10. installed so the operating instructions are clearly visible.

Note: New fire extinguishers are not required to be serviced and tagged, as long as the seller or agent can provide proof of purchase upon request.

#### MONITORED SYSTEMS INFORMATION:

- 1. Have the system(s) put into "test mode" for two hours from the time of a scheduled inspection; and
- 2. When a monitored system is present/in use, someone who knows how to reset the signaling device and each smoke detector head must be present for the inspection.

As of November 1, 2005, working smoke alarms, portable fire extinguishers, and carbon monoxide detectors are required for all one and two family dwellings, including townhomes and condos, per N.J.A.C 5:70-4.19.

## **SMOKE DETECTOR REQUIREMENTS** BY YEAR ORIGINAL HOME WAS APPROVED

Per NJ state law, all homes built after January 1, 1977 must have at least one hardwired alarm.

In addition to the requirement above, the following requirements also apply:

#### BEFORE 11/07/1984

Ten-year sealed battery smoke detectors on all living levels including basement. If the home was built between 1/1/77 and 11/7/84, at least one level of the home must have a hardwired detector, and all other detectors must be 10 year sealed units. The location on the sleeping level(s) shall be in hallway outside of all bedrooms.

In buildings of Use Group R-3, smoke detectors shall be required on every story of the unit including basements. In dwelling units with <u>split levels</u>, a smoke detector installed on the upper level shall suffice for the adjacent lower level provided the lower level is less than one full story below the upper level. If there is an intervening door between the adjacent levels, a smoke detector shall be installed in an approved location. Where more than one detector is required

to be installed within an individual dwelling unit, the detectors shall be wired in such a manner than the actuation of

one alarm will actuate all the alarms in the individual unit.

AFTER 11/07/1984 (Per BOCA 1984 Section 1716.3.4)

### AFTER 11/01/1993 (Per Section 919.3.2)

Use Groups R-2 & R-3 (now R-3, R-4, R-5), single or multiple-station smoke detectors shall be installed and maintained in all occupancies at the following locations: 1) in the immediate vicinity of bedrooms, 2) in all bedrooms, and 3) in each story within a dwelling unit, including basements.

#### **Exceptions:**

1) In dwelling units with split levels (see <u>split levels</u> above), and 2) In bedrooms that are equipped with residential sprinklers in accordance with Section 906.2.1, 906.2.2 or 906.2.3.

**Note**: If the home has a monitored or hardwired system, it **CANNOT** be reverted to a battery only system.

# **SMOKE DETECTOR REQUIREMENTS** FOR RESIDENTIAL ADDITIONS

If the cumulative area of all floors of the addition(s) is five percent (5%) or more, but less than twenty-five percent (25%), of the floor area of the largest floor of the existing building, hardwired interconnected smoke detectors with battery back-up meeting the requirements of NFPA 72 (except as otherwise provided in the building or Fire Protection Subcode, shall be installed and maintained in each story in the dwelling unit, including basements.

If the area of the addition is twenty-five percent (25%) or more of the floor area of the largest floor of the existing building, smoke detectors must be installed in each bedroom, one in the hallway outside of the bedrooms, and on each floor including the basement. These detectors must be interconnected, electric and battery back-up.

#### SMOKE DETECTOR INSTALLATION TIPS

For best performance, do not install units:

- where combustion particles, which form when things are burned, are produced. Areas to avoid include poorly ventilated kitchens, garages, and furnace rooms. Keep units at least 20 feet (8 meters) from the sources of combustion particles, including stoves, furnaces, water heaters, space heaters. Those areas should be vented as much as possible.
- in air streams near a kitchen. Air currents can draw cooking smoke into the sensing chamber;
- in very damp, humid or steamy areas, such as near bathrooms with showers. Keep units at least 10 feet (3 meters) away from showers, saunas, dishwashers, etc.;
- where the temperatures are regularly below 40°F (4°C) or above 100°F (38°C), including unheated buildings, outdoor rooms, porches, or unfinished attics or basements;
- in dusty, dirty, or greasy areas, such as directly over a stove or range. Be sure to clean a laundry room unit frequently to keep it free of dust or lint;
- near fresh air vents, ceiling fans, or in drafty areas as they may prevent detectors from reaching the sensing chamber;
- in insect-infested areas. Insects can clog openings to the sensing chamber and cause false alarms;
- less than 12 inches (305mm) away from fluorescent lights. Electrical "noise" can cause interference;
- in "dead air" spaces. "Dead air" spaces may prevent smoke from reaching the smoke detector.

AS OF JANUARY 1, 2019, ALL SINGLE STATION BATTERY-POWERED SMOKE ALARMS MUST BE 10-YEAR SEALED DEVICES.